





REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 09/20/05'	~	LJC 09/20/05'
B	料号中增加尺寸DIM. H, E选项	YCH 07/18/08'	~	




V/T TYPE



R/A TYPE



Elevator TYPE



Dimension

Position	A	B	C				
10	20.30	18.10	10.16	30	45.70	43.50	35.56
12	22.84	20.64	12.70	34	50.78	48.58	40.64
14	25.38	23.18	15.24	40	58.40	56.20	48.26
16	27.92	25.72	17.78	50	71.10	68.90	60.96
20	33.00	30.80	22.86	60	83.80	81.60	73.66
26	40.62	38.42	30.48	64	88.88	86.68	78.74

NOTES:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 20mΩ Max. INITIAL.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000MΩ Min.
- ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE RANGE: -45°C~+105°C.
- PART NUMBER: DS1013
- PRODUCT NUMBER CODE: DS1013- X X X X X X

DIM. H TYPE (FOR ELEVATOR ONLY)
1: 7.50
2: 9.50


DIM. E TYPE (FOR V/T ONLY)
1: 3.10
2: 8.00

HOUSING COLOR
B: BLACK
W: WHITE
U: BLUE
A: GRAY

CONTACT PLATING
Si: FULL GOLD FLASH

MOUNTING TYPE
S: V/T TYPE
R: R/A TYPE
E: Elevator TYPE

No.OF CONTACTS
08 10 14 16
20 26 30 34
40 50 60 64



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	TITLE	BOX HEADER PITCH 2.54mm
X. ±0.60	X. ±5°	UNITS	mm	
.X ±0.38	.X ±3°	SHEET SIZE	A4	SERIES DS1013 SERIES
.XX ±0.25	.XX ±2°	晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD		
DRAWING TYPE	CUSTOMER	Add: West Gao Xing Road, Gao Xing, Ningbo, China Tel: 86-574-63508787 Fax: 86-574-63510817 Http://www.connfly.com.cn		
SCALE	1:1	SHEET	1 OF 1	
DRAWING NO.	C-DS1013-XXXX-B			