

1



### GLC1-DN series magnetic contactors 3 pole

Standard power ratings of 3-phase motors 50/60 Hz in category AC-3						Rated operational current in AC-3 up to 440V (A)	Rated operational current in AC-1 up to 440V (A)	Rated nonconductive voltage (V)	Instantaneous auxiliary contacts		Reference
220V 230V (kW)	380V 400V (kW)	415V (kW)	440V (kW)	500V (kW)	660V 690V (kW)						
2.2	4	4	4	5.5	5.5	9	25	690	1	1	GLC1-DN0911
3	5.5	5.5	5.5	7.5	7.5	12	25	690	1	1	GLC1-DN1211
4	7.5	9	9	10	10	18	32	690	1	1	GLC1-DN1811
5.5	11	11	11	15	15	25	40	690	1	1	GLC1-DN2511
7.5	15	15	15	18.5	18.5	32	50	690	1	1	GLC1-DN3211
11	18.5	22	22	22	30	40	60	690	1	1	GLC1-DN4011
15	22	30	30	30	33	50	80	690	1	1	GLC1-DN5011
18.5	30	37	37	37	37	65	80	690	1	1	GLC1-DN6511
22	37	45	45	45	45	80	125	690	1	1	GLC1-DN8011
25	45	45	45	45	45	95	125	690	1	1	GLC1-DN9511