




ROHS COMPLIANT

REVISIONS			
REV	ECN NO.	DESCRIPTION	APPROVED BY DATE

**Product Specification**


Material  
 Insulator :Glass-Filled Thermoplastic  
 PBT or PPS UL94V-0 rates  
 Contact :Phosphor Bronze,  
 Plated full gold or selected gold in  
 mating area, 100u" min. tin-lead on  
 on termination area, with entire contact  
 under-plated 50u" min. Nickel  
 Electrical  
 Contact Resistance :30 milliohms  
 Max at 1 AMP DC.  
 Insulation Resistance :1000  
 megohms at 500 VDC  
 Dielectric Withstanding Voltage :  
 500 VAC/rms 60Hz for 1 minute  
 Current Rating :1 AMP  
 Voltage Rating :250 VAC/rms 60Hz



**Dimensions**

Positions	A	B	C	D
20	5.08	15.50	5.08	15.50
28	7.62	18.04	7.62	18.04
32	7.62	18.04	10.16	20.50
44	12.70	23.48	12.70	23.48
52	15.24	25.88	15.24	25.88
68	20.32	31.04	20.32	31.04
84	25.40	36.04	25.40	36.04

Recommended PCB Layout



DIMENSIONS: <input type="checkbox"/> mm [INCH] <input type="checkbox"/> INCH [mm] <input checked="" type="checkbox"/> mm ONLY	CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE DRAWN BY AND DATE	TITLE <p style="text-align: center;">P.L.C.C. SOCKET</p>
UNLESS OTHERWISE SPECIFIED, GENERAL TOLERANCE: DECIMALS [0.015]    ANGLES X +0.38 [0.015]    X° ±3° XX +0.25 [0.010]    X° ±10° XXX +0.13 [0.005]	CHECKED BY AND DATE APPROVED BY AND DATE THIRD ANGLE PROJECTION	DRAWING NO. REV
FINISH	SCALE: 5 : 2    SIZE: A3	FILE NO.:    SHEET 1 OF 1

