

K18. Gegenmutter – Edelstahl

K18. Lock Nut – stainless steel



VA 1.4305, blank, mit Pg-Gewinde
Art.-Gruppe: K18.

Stainless steel AISI 303, bright, Pg connection thread
Art.-group: K18.

Abb. 1
Fig. 1




Abb. 2
Fig. 2

Nenngröße Rated size	Artikel-Nummer Art.-No.	C mm	Schlüsselweite Spanner width SW x E mm	
A				
Pg 7	749/5stv	2,8	17x19	50
Pg 9	750/5stv	2,8	22x24,4	50
Pg 11	751/5stv	3	22x24,4	50
Pg 13,5	752/5stv	3	24x26,7	50
Pg 16	753/5stv	3	27x29,5	50
Pg 21	754/5stv	3,5	32x35,5	50
Pg 29	755/5stv	4	41x45	50
Pg 36	756/5stv	5	50x54	25
Pg 42	757/5stv	5	60x65	10
Pg 48	758/5stv	5,5	64x69	10

K19. Gegenmutter – Polyamid

K19. Lock Nut – polyamide



Polyamid-GFK, Farbe: RAL 7035 (hellgrau)
mit metrischem Gewinde nach EN 60 423
Temperaturbereich: -40 °C bis +100 °C
Art.-Gruppe: K19.

Polyamide-GFK, Colour: RAL 7035 (light grey)
with metric thread as per EN 60 423
Temperature range: -40 °C up to +100 °C
Art.-group: K19.

Abb. 1
Fig. 1




Abb. 2
Fig. 2

Nenngröße Rated size	Artikel-Nummer Art.-No.	C mm	Schlüsselweite Spanner width SW x E mm	
A				
M12x1,5	1420/212	5	17x19	50
M16x1,5	1420/216	5	22x25	50
M20x1,5	1420/220	6	27x30	50
M25x1,5	1420/225	6	32x36	50
M32x1,5	1420/232	7	41x46	50
M40x1,5	1420/240	7	50x54	25
M50x1,5	1420/250	8	60x67	10
M63x1,5	1420/263	8	75x82	10