

CM30



[Specification PDF Download](#)



[Bookmark This Page](#)



[Print This Page](#)



[Tell A Friend](#)



[Live Messenger](#)



[Skype Me](#)



Peter@greegoo.com

[Send Inquiry](#)

[Add to Inquiry Basket](#) | [View Inquiry Basket](#)

Capacitance Proximity Sensors CM30

Model explanation of Capacitance Proximity Sensors

$\frac{G}{1} \frac{18}{2} - \frac{3}{3} \frac{A}{4} \frac{10}{5} \frac{N}{6} \frac{A}{7} \frac{\square}{8}$

1. Switch category(LM: inductance type; CM: capacitance type; SM:Hall type; AM:safety explosion-proof type; XM: mimic linear type)
2. Outward appearance code(■: Cylinder type; F: Angular column type and plane installation type)
3. Operating voltage(30: 6-36VDC; 310: 5-24VDC; 320: 12-60VDC; 20: 90-250VAC; 210: 24-250VAC; 220: 380VAC; 40: 12-240VDC/24-240AC; 50: Special voltage)
4. Detection distance(01: 1mm; 05:5mm; 10:10mm)
5. Output method (N: Three-line DC NPN output; P: Three-line DC PNP output; L: Two-line DC output; ■: AC two-wire output; J: Relay output; NP: NPN+PNP output)
6. Output status(A: NO; B: NC; C: NO+NC; MU: Mimic voltage; MI: Mimic current)
7. Auxil function code(T: With connector; Y: Water proof, oil proof; I: Special requirement; H: High temp resistance; R: Ring type)

Main features

- Compact volume
- high precision of repeated location
- Diversified exterior structures
- Good performance of anti-interference.
- Many output forms
- High on-off frequency.
- Wide voltage range
- Dust proof,vibration proof,water proof and oil proof.
- With short-circuit protection and inverted connecting protection.
- Long service life

Technical Parameters

Model NO.	Detection distance	Working voltage	Output		Flush
			Form	State	
CM30-3010NA	0-10mm	DC6-36V	NPN	NO	Flush
CM30-3010NB	0-10mm	DC6-36V	NPN	NC	Flush
CM30-3010NC	0-10mm	DC6-36V	NPN	NO+NC	Flush
CM30-3010PA	0-10mm	DC6-36V	PNP	NO	Flush
CM30-3010PB	0-10mm	DC6-36V	PNP	NC	Flush

CM30-3010PA	0-10mm	DC6-36V	PNP	NO	Flush
CM30-3010PB	0-10mm	DC6-36V	PNP	NC	Flush
CM30-3010PC	0-10mm	DC6-36V	PNP	NO+NC	Flush
CM30-2010A	0-10mm	AC90-250V	SCR Control lable silicon	NO	Flush
CM30-2010B	0-10mm	AC90-250V	SCR Control lable silicon	NC	Flush
CM30-3015NA	0-15mm	DC6-36V	NPN	NO	Non-flush
CM30-3015NB	0-15mm	DC6-36V	NPN	NC	Non-flush
CM30-3015NC	0-15mm	DC6-36V	NPN	NO+NC	Non-flush
CM30-3015PA	0-15mm	DC6-36V	PNP	NO	Non-flush
CM30-3015PB	0-15mm	DC6-36V	PNP	NC	Non-flush
CM30-3015PC	0-15mm	DC6-36V	PNP	NO+NC	Non-flush
CM30-2015A	0-15mm	AC90-250V	SCR Control lable silicon	NO	Non-flush
CM30-2015B	0-15mm	AC90-250V	SCR Control lable silicon	NC	Non-flush

