




GX700-DFR



-  [Bookmark This Page](#)
-  [Print This Page](#)
-  [Tell A Friend](#)
-  [Live Messenger](#)
-  [Skype Me](#)
-  Peter@greegoo.com

[Send Inquiry](#)

[Add to Inquiry Basket](#) | [View Inquiry Basket](#)

Photo sensor (Ben series)

Type	Free voltage, Relay contact output	
Model	Diffuse	
	GX700-DFR	
Dimension	W25*H67*L81	
Detecting distance	700mm(200*200mm Non glossy white paper)	
Detecting target	Transpqrnt, Translucent, Opaque materials	
Hysteresis	Max.20% at detecting distance	
Response time	Max.20mS	
Power supply	24 TO 240VAC±10%50/60Hz, 24-240VDC±10%(Ripple P-P: Max10%)	
Sensitivity	Adjustable by VR	
Operating	Selectable light ON/D or Dark ON by slide switch	
Control output	Relay contact output	Capacity:30VDC 3A Resistive load, 250VAC 3A resistive load
		Contact orde: 1C
Self-diagnostic output	Green LED turns on at unstable operation	
Timer function	ON delay, OFF delay, selectable one shot delay by slide switch	
	Delay time: 0.1 to 5 sec adjustable by VR	
Protection	IP54(IEC Standard)	