



## DK...-TF

DK...-TF series is the DIN Rail terminal block with fuse, which is designed for fitting both TS-35 and TS-32 DIN Rails. According to the needed requirement, the series can be installed with LED indicator. DK...-TF series are fitted with the standard fuse of diameter of 5mm. In addition, with the upper unsealed switch, it is easy to change the fuse.

## DK...-TF



DK4-TF(5X20)



DK4-TFL(5X20)



DKK4-TF(5X20)

Approval	UL IEC	
Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	16A	6.3A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	24~12 / 0.5~4	
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	24~12 / 0.5~4	
Rated impulse withstand voltage	6KV	
Torque(N-m)	0.8	
Screw	M3	
Wire strip length	10~12mm	
Insulating material	PA	
TxHxW(mm)	8 x 54.6 x 60	
Optional color	Cat. No.	

Approval	UL IEC	
Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	16A	6.3A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	24~12 / 0.5~4	
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	24~12 / 0.5~4	
Rated impulse withstand voltage	6KV	
Torque(N-m)	0.8	
Screw	M3	
Wire strip length	10~12mm	
Insulating material	PA	
TxHxW(mm)	8 x 54.8 x 56	
Optional color	Cat. No.	

Approval	UL IEC	
Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	16A <sup>1)</sup> 30A <sup>2)</sup>	16A <sup>1)</sup> 30A <sup>2)</sup>
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	22~10 / 0.5~4	
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	22~10 / 0.5~4	
Rated impulse withstand voltage	6KV	
Torque(N-m)	0.67	
Screw	M3.5	
Wire strip length	10~12mm	
Insulating material	PA	
TxHxW(mm)	8 x 55.9 x 72.5	
Optional color	Cat. No.	

1) upper level  
2) lower level  
UL 600V / 5A

Accessories	Cat. No.
	DK4C-TF(5X20)

Accessories	Cat. No.
	DK4C-TF(5X20)

Accessories	Cat. No.
	DKK4C-TF(5X20)

End cover

Partition

Small partition

Insertion bridge

Insertion bridge

Screw-on bridge

Marking label

Mounting Rail

Tool

2 way	CSC-602PN
:	:
:	:
10way	CSC-610PN

CSC-602PN
:
:
CSC-610PN

TM28
TS-35 / TS-32
0.5 x 3mm

TM28
TS-35 / TS-32
0.5 x 3mm

TM28
TS-35 / TS-32
0.5 x 3mm

Nom Voltage	Cat. No.
5V	DK4-TFL5 (5x20)
12V	DK4-TFL12 (5x20)
24V	DK4-TFL24 (5x20)
48V	DK4-TFL48 (5x20)
110V	DK4-TFL110 (5x20)
220V	DK4-TFL220 (5x20)
300V	DK4-TFL300 (5x20)




**DK10-TF(5X20)**




**DK10-TFA(5X20)**







**0032-4002**

Approval 		
Technical Data	UL	IEC
Rated voltage	600V	800V
Rated current	6.3A	6.3A
Conductor cross-section, solid( AWG/mm <sup>2</sup> )	22~6 / 1.5~10	
Conductor cross-section, flexible ( AWG/mm <sup>2</sup> )	22~6 / 1.5~10	
Rated impulse withstand voltage	6KV	
Torque(N-m)	1.8	
Screw	M4	
Wire strip length	12~16mm	
Insulating material	PA	
TxHxW(mm)	12 x 47.2 x 61.63	
Optional color	Cat. No.	

Approval 		
Technical Data	UL	IEC
Rated voltage	600V	660V
Rated current	6.3A	6.3A
Conductor cross-section, solid( AWG/mm <sup>2</sup> )	22~6 / 1.5~10	
Conductor cross-section, flexible ( AWG/mm <sup>2</sup> )	22~6 / 1.5~10	
Rated impulse withstand voltage	6KV	
Torque(N-m)	1.8	
Screw	M4	
Wire strip length	12~16mm	
Insulating material	PA	
TxHxW(mm)	12 x 47.2 x 61.63	
Optional color	Cat. No.	

Approval		
Technical Data	UL	IEC
Rated voltage		
Rated current		
Conductor cross-section, solid( AWG/mm <sup>2</sup> )		
Conductor cross-section, flexible ( AWG/mm <sup>2</sup> )		
Rated impulse withstand voltage		
Torque(N-m)		
Screw		
Wire strip length		
Insulating material		
TxHxW(mm)	26 x 58 x 51	

Accessories	Cat. No.
End cover 	
Partition	
Small partition	
Insertion bridge 	
Insertion bridge 	
Screw-on bridge 	
Marking label 	TM20
Mounting Rail 	TS-35 / TS-32
Tool 	0.6 x 3.5mm

Accessories	Cat. No.
End cover	
Partition	
Small partition	
Insertion bridge	
Insertion bridge	
Screw-on bridge	
Marking label	TM20
Mounting Rail	TS-35 / TS-32
Tool	0.6 x 3.5mm

Accessories	Cat. No.
End cover	
Partition	
Small partition	
Insertion bridge	
Insertion bridge	
Screw-on bridge	
Marking label	
Mounting Rail	
Tool	