

## DIGITAL MULTIMETER

### MY63/MY64/MY65

#### Features:

- ▶ Rugged Shell Design
- ▶ Large Digital LCD Display
- ▶ Tests AC/DC Voltage and Current, Resistance, Capacitance and Frequency
- ▶ Transistor Check, Diode and Continuity Test
- ▶ Type-K thermocouple contact temperature measurement (MY64)
- ▶ Data Hold and Auto Power Off

EMC  
LVD



#### Specifications

MY63 MY64 MY65


Specifications	Range	MY63	MY64	MY65
DC Voltage	200mV/2V/20V/200V	±(0.5%+3)	±(0.5%+3)	±(0.1%+3)
	1000V	±(0.8%+3)	±(0.8%+3)	±(0.15%+3)
AC Voltage	2V/20V/200V	±(0.8%+3)	±(0.8%+3)	±(0.6%+10)
	750V	±(1.2%+3)	±(1.2%+3)	±(0.8%+15)
DC Current	2mA/20mA/200mA	±(1.5%+1)	±(1.5%+1)	±(0.8%+5)
	10A	±(2.0%+5)	±(2.0%+5)	±(2.0%+10)
AC Current	2mA/20mA/200mA	±(1.8%+5)	±(1.8%+5)	±(0.8%+10)
	10A	±(3.0%+5)	±(3.0%+5)	±(2.0%+10)
Resistance	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+3)	±(0.8%+3)	±(0.5%+3)
	20MΩ	±(1.0%+5)	±(1.0%+5)	±(0.5%+1)
	200MΩ	±(6.0%+10)	±(6.0%+10)	±(5.0%+10)
Capacitance	2nF/20nF/200nF/2μF	±(4.0%+3)	±(4.0%+3)	
	20nF/200nF/2μF/20μF			±(4.0%+20)
	100μF	±(6.0%+10)	±(6.0%+10)	±(6.0%+10)
Frequency	20kHz		±(1.5%+5)	±(1.5%+5)
	2kHz/20kHz	±(1.5%+5)		
Temperature(°C)	-20°C~1000°C		±(2%+2)	
<b>Functions</b>				
Display	counts	2000	2000	20000
Transistor hFE	0~1000	●	●	●
Diode	2.7V	●	●	●
Continuity Buzzer	<50Ω	●	●	●
Data Hold		●	●	●
Apo	Auto Power Off	●	●	●
LBD	Low Battery Display	●	●	●
<b>General</b>				
Power Supply	1×9V 6F22 Battery			
Product Size	195mm×95mm×55mm/7.67"×3.74"×2.16"			
Product Weight	366g/0.8lb			
Safety Rating	CE ETL CAT.II 1000V CAT.III 600V RoHS			



#### MY63

**VOLTAGE** AC 750V  
DC 1000V


**CURRENT** AC 10A  
DC 10A



#### MY64

**VOLTAGE** AC 750V  
DC 1000V

**CURRENT** AC 10A  
DC 10A



#### MY65

**VOLTAGE** AC 750V  
DC 1000V

**CURRENT** AC 10A  
DC 10A

