

# BUELA 30 K

datasheet for BUELA 30 K  
article number: 930727100



[View Full-Size Image](#)

**SKS**<sup>®</sup>  
SKS Kontakttechnik GmbH

<b>product description:</b>		order number: 930 727-100
<b>description:</b>	Multiple-spring wire plug, shatter-proof, flexible insulated sleeve with transverse hole. The tapering sleeve end also serves as kinking protection for the lead. Solder connection up to maximum cable cross-section of 2.5 mm <sup>2</sup> . Nickel-plated brass contact material.	
<b>typ:</b>	BUELA 30 K schwarz/black	
<b>system:</b>	4mm system	
<b>order number:</b>	930 727-100	
<b>color:</b>	●	
<b>other color versions:</b>	● ● ● ● ● ○	
<b>technical data</b>		
<b>measurement category acc. to IEC 61010:</b>	CAT I	
<b>pin dimensions</b>	4 mm	
<b>type of contact:</b>	pin (spring loaded)	
<b>type of termination:</b>	solder	
<b>rated voltage:</b>	30 VAC / 60 VDC	
<b>rated current:</b> <i>Please consider derating curve!</i>	30 A	
<b>contact resistance:</b>	3 mOhm	
<b>material</b>		
<b>contact material:</b>	brass	
<b>contact surface material:</b>	nickel	
<b>housing material:</b>	PVC - P	
<b>environmental conditions:</b>		
<b>temperature range:</b>	-25 °C to +70 °C	
<b>drawing</b>		