




SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈


S150 Series SMD Chip LED Lamps

Part Number: Q150YUS4

Package outlines



RECOMMEND PAD LAYOUT





ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
SENSITIVE DEVICES

| ITEM | MATERIALS |
|-----------------------|-------------------|
| Resin (mold) | Epoxy |
| Bonding Wire | Ø 25 µm Au |
| Lens color | Water transparent |
| Printed circuit board | BT (white) |
| Dice | AlGaInP |
| Emitted color | Yellow |

NOTES:

1. All dimensions are in millimeters (inches);
2. Tolerances are ±0.1mm (0.004inch) unless otherwise noted.

| | | | |
|--|--|--|--|
| | | | |
| | | | |

SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈

Part Number: Q150YUS4

Absolute maximum ratings (T_A=25°C)

| Parameter | Symbol | Value | Unit |
|---|------------------|----------|------|
| Forward current | I _f | 30 | mA |
| Reverse voltage | V _r | 5 | V |
| Power dissipation | P _d | 75 | mW |
| Operating temperature range | T _{op} | -20 ~+80 | °C |
| Storage temperature range | T _{stg} | -20 ~+80 | °C |
| Peak pulsing current (1/8 duty f=1kHz) | I _{fp} | 125 | mA |

Electro-optical characteristics (T_A=25°C)

| Parameter | Test Conditio n | Symbo l | Value | | | Unit |
|-------------------------------------|-----------------------|-------------------|-------|-----|-----|------|
| | | | Min | Typ | Max | |
| Wavelength at peak emission | I _f =20mA | λ _{peak} | 590 | 595 | 600 | nm |
| Spectral half bandwidth | I _f =20mA | Δλ | -- | 20 | -- | nm |
| Dominant wavelength | I _f =20mA | λ _{dom} | -- | 590 | -- | nm |
| Forward voltage | I _f =20mA | V _f | -- | 2.0 | 2.5 | V |
| Luminous intensity * 1 | I _f =20mA | I _v | | 600 | -- | mcd |
| Viewing angle at 50% I _v | I _f =10mA | 2θ _{1/2} | -- | 140 | -- | Deg |
| Reverse current | V _r =5V | I _r | -- | -- | 10 | μA |

* 1 Note: Luminous intensity tolerance is $\pm 10\%$.


SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈


Part Number: Q150YUS4

OPTICAL CHARACTERISTIC CURVES


Relative Intensity vs. Wavelength



Forward Current vs. Forward Voltage



Directive Characteristics




SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈

Reflow Profile

■ Reflow Temp/Time




■ Soldering iron

Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter

($+10^{\circ}\text{C} \rightarrow -1\text{sec}$). Power dissipation of iron should be smaller than 15W, and temperatures should be controllable. Surface temperature of the device

■ Rework

1. Customer must finish rework within 5 sec under 260°C .
2. The head of iron can not touch copper foil
3. Twin-head type is preferred.




SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈

Test circuit and handling precautions

■ Test circuit



■ Handling precautions

1. Over-current-proof

Customer must apply resistors for protection; otherwise slight voltage shift will cause

big current change (Burn out will happen).

2. Storage

2.1 It is recommended to store the products in the following conditions:

Humidity: 60% R.H. Max.

Temperature : 5°C~30°C (41°F~86°F)

2.2 Shelf life in sealed bag: 12 month at < 5°C~30°C and < 30% R.H. after the package is

Opened, the products should be used within a week or they should be keeping to stored at

≤20 R.H. with zip-lock sealed.

3. Baking

It is recommended to baking before soldering when the pack is unsealed after 72hrs. The

Conditions are as followings:

3.1 60±3°C x(12~24hrs) and < 5%RH, taped reel type

3.2 100±3°C x(45min~1hr), bulk type

3.3 130±3°C x(15~30min), bulk type

SURFACE MOUNT LED LAMPS

表面黏著型發光二極體指示燈

Test items and results of reliability

| Type | Test Item | Test Conditions | Note | Number of Damaged |
|-------------|------------------------------|---|-----------|-------------------|
| Requirement | Temperature Cycle | -20°C 30min ↑↓ 80°C 30min | 100 cycle | 0/22 |
| | Thermal Shock | -20°C 15min ↑↓ 80°C 15min | 100 cycle | 0/22 |
| | High Humidity Heat Cycle | 30°C↔ 65°C 90%RH 24hrs/1cycle | 10 cycle | 0/22 |
| | High Temperature Storage | T _a =80°C | 1000 hrs | 0/22 |
| | Humidity Heat Storage | T _a =60°C RH=90% | 1000 hrs | 0/22 |
| | Low Temperature Storage | T _a =-30°C | 1000 hrs | 0/22 |
| SeOperation | Life Test | T _a =25°C I _F =20mA | 1000 hrs | 0/22 |
| | High Humidity Heat Life Test | 60°C RH=90% I _F =20mA | 500 hrs | 0/22 |
| | Low Temperature Life Test | T _a =-20°C I _F =20mA | 1000 hrs | 0/22 |