



PC 16

Approval		
Capability		
Standard	UL	IEC
Rated Voltage	600V	800V
Rated Current	85A	76A
Wire size	12-4AWG	0.2-16mm ²
T/W/End plate		12.2/42.5/1.5mm
Height(mm)(NS35:7.5/NS35:15/NS32)		54/61.5/59mm
Rated surge voltage/Contamination Class		8KV/3
Stripping length		11mm
Screw thread/Tightening torque		M4/1.2N.m/10.5Lb-in
Internal cylindrical gage		B7
Insulating Material/Inflammability class		PAV-0
Specification	Model	Pieces
(1) Terminal block	PC 16	50
(2) End cover	D-PC 16	50
(3) Fixed bridge		
2-P		
3-P		
5-P		
10-P		
(4) Step bracket	FBI 10-12	10
(5) Insertion bridge		
2-P		
3-P		
10-P		
(6) Isolator bridge bar, 10P	EB 10-12	10
(7) Bridge bar isolator		
(8) Switching bridge		
(9) Separating plate	TS-K	50
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 47/16	100
(12) Test plug socket, insulated	DSBJ 47/15/6	
(13) Zack strip	ZB10	

HOW TO ORDER :

- **P** - **1** -

X X X X X X X

Customer Request

1	Gray	4	Green	7	Transparent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	White

Color

Series No. No. of pole

mm
(INCH)



DEGSON®



DEGSON ELECTRONICS CO., LTD.

NAME

PC 16