

UNI-T®

UTD2000L SERIES
 Digital Storage Oscilloscopes
 UTD2025CL(NEW) ▪ UTD2052CL



SPECIFICATIONS		
Specifications	UTD2025CL	UTD2052CL
Channels	2	
Bandwidth	25MHz	50MHz
Sample Rate	250Ms/s	500Ms/s
Rise Time	≤14ns	≤7ns
Memory Depth	25kpts	
Waveform Acquisition Rate	≥2000wfms/s	
Vertical Sensitivity	1mV/div~20V/div	
Time-Based Range	10ns/div~50s/div	5ns/div~50s/div
Storage	Setup, Wave, Bitmap	
Trigger Modes	Edge, Pluse, Video, Alternate	
Interface	USB OTG, Pass/Fail	USB OTG

GENERAL CHARACTERISTICS	
Power	100-240VAC, 40-440Hz
Display	7 Inches 64K Color TFT LCD, (320×240)
Product Color	Red and Gray
Product Net Weight	2.2Kg
Product Size	306mm ×147mm × 122mm
Standard Accessories	Probe×2 (1×, 10× switchable), Power Cord, USB Cable, PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 PCs
Standard Carton Measurement	450mm × 420mm × 280mm (0.053 CBM Per Standard Carton)
Standard Carton Gross Weight	8.5Kg