



Codice Order number

versione version	n. poli n. poles	bussola contact terminal	Ø min-max cavo Ø cable min-max	pz/imb pcs/box	codice order number
 <p>IP68 2 BAR max voltage 450 V max current 32 A</p>	2		A 7.0 mm - 10.5 mm	200	THB.390. E2A.1
			A 10.5 mm - 14.0 mm	200	THB.390. E2A.2
			A 14.0 mm - 17.0 mm	200	THB.390. E2A.3
			A 7.0 mm - 10.5 mm	200	THB.390. E2C.1
			A 10.5 mm - 14.0 mm	200	THB.390. E2C.2
			A 14.0 mm - 17.0 mm	200	THB.390. E2C.3
	3		A 7.0 mm - 10.5 mm	200	THB.390. E3A.1
			A 10.5 mm - 14.0 mm	200	THB.390. E3A.2
			A 14.0 mm - 17.0 mm	200	THB.390. E3A.3
			A 7.0 mm - 10.5 mm	200	THB.390. E3C.1
			A 10.5 mm - 14.0 mm	200	THB.390. E3C.2
			A 14.0 mm - 17.0 mm	200	THB.390. E3C.3
 <p>IP68 2 BAR max voltage 450 V max current 32 A</p>	2		A 7.0 mm - 10.5 mm	200	THB.390. F2A.1
			A 10.5 mm - 14.0 mm	200	THB.390. F2A.2
			A 14.0 mm - 17.0 mm	200	THB.390. F2A.3
			A 7.0 mm - 10.5 mm	200	THB.390. F2C.1
			A 10.5 mm - 14.0 mm	200	THB.390. F2C.2
			A 14.0 mm - 17.0 mm	200	THB.390. F2C.3
	3		A 7.0 mm - 10.5 mm	200	THB.390. F3A.1
			A 10.5 mm - 14.0 mm	200	THB.390. F3A.2
			A 14.0 mm - 17.0 mm	200	THB.390. F3A.3
			A 7.0 mm - 10.5 mm	200	THB.390. F3C.1
			A 10.5 mm - 14.0 mm	200	THB.390. F3C.2
			A 14.0 mm - 17.0 mm	200	THB.390. F3C.3
Le versioni sopra indicate sono disponibili con terminali a perforazione di isolante. The above versions are available with piercing clip terminal blocks.				200	THP.390.XXA.X
Note:	Bussola cieca End barrier contact	Bussola WP per sezione cavo WP contact for cable section < 1.0 mm²			
	Bussola a perforazione max 1.5 mm² Piercing clip terminals max 1.5 mm²				