



REV. 更改	DESCRIPTION 说明	ENG. 修改人	APPROVE 审核

PANEL CUTOUT
MAX.PANEL THICKNESS
6.0mm

Contact Composition

Seal Ring

Part Number:

LAS1-APY - □TS / ◎

"□"	Contact structure	"◎"	IP Class
11	1NO 1NC	No Letter	IP40
22	2NO 2NC	P	IP65

SPECIFICATIONS:

- 1.Max.Switch Rating: Ith:5A Ui: 250VAC.
- 2.Rating:0.5A 250VAC.
- 3.Electrical Life: ≥50,000cycles.
- 4.Contact Resistance: ≤50mΩ.
- 5.Insulation Resistance: ≥100MΩ.
- 6.Dielectric Strength: 2,000V RMS 50Hz.
- 7.Operating Temperature: -20℃~ +55℃.
- 8.IP Class: IP40 (IP65 Made to order).

MATERIALS:

- 1.Button: PBT.
- 2.Contact: Silver alloy.
- 3.Nut: PC.
- 4.Base: PBT.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

中国·红波按钮制造有限公司
ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

USED 用途	APPD 审核	CH 2013/11/09
FINISH 处理	CHKD 校对	NCH 2013/11/09
DIMENSIONS	TOLERANCE	SCALE
0.00 TO 30.00mm	±0.20mm	比例 1.2 / 1
30.01 TO 80.00mm	±0.25mm	UNIT mm
80.01 TO 150.00mm	±0.30mm	DR. 制图
150.01 ↑	±0.40mm	WWX 2013/11/09

TITLE
名称 Emergency Stop Switch

DWG NO.
图号 LAS1-APY - □TS / ◎

SIZE
图纸 A4

FILE NAME
档案名称 LAS1-A22011.DWG

SHEET
张 1 / 1

REV.
更改 1