

ROCKER SWITCH

Features

- Power switch conforms to safety standards for electrical equipment.
- Compact with a good space factor.
- Snap-in type for easy mounting.
- The color can be changed to correspond to the set design.



E88392 

Applications

- Information and office equipment such as personal computers, word processors, facsimiles, monitors, etc.

Specifications

ITEM

STANDARD


Rating	10A 125V AC/ 6A 250V AC, 4A 125VAC/2A 250VAC
Insulation Resistance	100M Ω min (DC 500V)
Dielectric Strength	AC 1500V (50/60Hz for 1 minute)
Contact Resistance	50m Ω max.
Electrically Life	10,000 cycle
Operating Force	400 \pm 200 gf

Product Selection

R9 —




SERIES	FUNCTION	ACTUATOR MARKING OPTION
2 <input type="checkbox"/> A	ON OFF	N NONE
3 <input type="checkbox"/> B	ON ON	P — ○
2 <input type="checkbox"/> C	ON OFF ON	Q ○
3 <input type="checkbox"/> D	(ON - OFF)	R ●
3 <input type="checkbox"/> E	(ON) - ON	S ○
3 <input type="checkbox"/> F	(ON)-OFF-(ON)	T $\frac{Z}{O}$ $\frac{LL}{O}$
2 <input type="checkbox"/> AL	ON OFF (With LED)	
32ALP	ON OFF (With Lamp)	

PANEL HOLE SIZE



PANEL THICKNESS	DIM. X	DIM. Y
0.75 ~ 1.25	19.2	13.0
1.25 ~ 2.0	19.4	13.0
2.0 ~ 3.0	19.6	13.0

Terminal Type

TERMINAL TYPE					
CODE	TERMINAL	CODE	TERMINAL	CODE	TERMINAL
2 PIN		3 Soldering		4 PCB	

HIGHLY

F1

Design, specifications are subject to change without notice.

ROCKER SWITCH

Dimensions

UNIT:mm

Item NO.	Dimensions	Function	Circuit												
R9-22A		<table border="1"> <tr><th colspan="2">SWITCHING FUNCTION</th></tr> <tr><td></td><td></td></tr> <tr><td>OFF</td><td>ON</td></tr> </table> <p>Panel hole size</p>	SWITCHING FUNCTION				OFF	ON							
SWITCHING FUNCTION															
OFF	ON														
R9-33B		<table border="1"> <tr><th colspan="2">SWITCHING FUNCTION</th></tr> <tr><td></td><td></td></tr> <tr><td>ON</td><td>ON</td></tr> </table> <p>Panel hole size</p>	SWITCHING FUNCTION				ON	ON							
SWITCHING FUNCTION															
ON	ON														
R9-24A		<table border="1"> <tr><th colspan="3">SWITCHING FUNCTION</th></tr> <tr><td></td><td></td><td></td></tr> <tr><td>ON</td><td>NONE</td><td>ON</td></tr> </table> <p>Panel hole size</p> <p>Mounting holes</p>	SWITCHING FUNCTION						ON	NONE	ON				
SWITCHING FUNCTION															
ON	NONE	ON													
R9-32F		<table border="1"> <tr><th colspan="3">SWITCHING FUNCTION</th></tr> <tr><th>CODE</th><td></td><td></td></tr> <tr><td>OFF</td><td>ON</td><td>OFF</td></tr> <tr><td>ALP</td><td>ON</td><td>OFF (With LAMP)</td></tr> </table> <p>Panel hole size</p>	SWITCHING FUNCTION			CODE			OFF	ON	OFF	ALP	ON	OFF (With LAMP)	
SWITCHING FUNCTION															
CODE															
OFF	ON	OFF													
ALP	ON	OFF (With LAMP)													

HIGHLY

F2

Design, specifications are subject to change without notice.