



Nr. / No.	Länge / length	Farbe / color
67189	0,2 m	
67999	0,5 m	
67185	0,5 m	
67890	1,0 m	
67188	1,0 m	
71221	2,0 m	

### USB 3.1 SuperSpeed+ Kabel

**Anschlüsse:** USB 3.1 Typ C-Stecker > USB 3.0 A-Stecker

**Material:** Isolation: PVC; schwarz  
Innenleiter: CU; AWG 28/32/34

**max. Datenrate:** 5 Gbit/s

**USB-Standard:** USB3.1/3.0,

**Kompatibilität:** USB2.0, 1.1

**Spannungsfestigkeit:** DC 300 V

**Isolationswiderstand:** 10 MΩ

**Kontaktwiderstand:** 2 Ω

**RoHS-konform**

### USB 3.1 SuperSpeed+ cable

**Connectors:** USB 3.1 Type C plug > USB 3.0 A plug

**Material:** Insulation: PVC; black  
Inner conductor: CU; AWG 28/32/34

**max. data rate:** 5 Gbitps

**USB standard:** USB3.1/3.0,

**Compatibiliy:** USB2.0, 1.1

**Dielectric strength:** DC 300 V

**Insulation resistance:** 10 MΩ

**Contact resistance:** 2 Ω

**RoHS compliant**

### Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
02.06.2016	jr	gez.:	31.01.2015	tf	USB 3.1 C/A 3.0	I
		gepr.:	31.01.2015	tf		
		Norm:	Änderungen vorbehalten / Subject to change			von



Zeichnungs-Nr.:  
von