


Customer 's name 客户名称：					Customer recognizes 客户承认：	
NO. 序号	Specified voltage and frequency 额定电压及频率	Specified capacity and capacity deviation 额定电容及电容偏差	Over all dimension 外形尺寸 (mm) ($\phi D \times H$) \pm	Remark 备注		
9	450VAC 50/60Hz	12 μ F \pm 5%	$\phi 35 \times 65$ M8			
10	450VAC 50/60Hz	16 μ F \pm 5%	$\phi 40 \times 70$ M8			
11	450VAC 50/60Hz	20 μ F \pm 5%	$\phi 40 \times 70$ M8			
12	450VAC 50/60Hz	25 μ F \pm 5%	$\phi 40 \times 95$ M8			
13	450VAC 50/60Hz	30 μ F \pm 5%	$\phi 40 \times 95$ M8			
Carry out standard 推行标准		GB 3667.1-2016/IEC60252-1: 2013				
Operating temp range 使用温度范围		-25 \sim +70 $^{\circ}$ C	Lifespan garden 寿命等级	C CLASS		
Withstanding standard 耐电压		Between terminals 端子相互间	2.0UN 2S no breakdown flashover 2.0UN 2S无击穿及飞弧现象			
		Terminals to case 端子与外壳间 (金属外壳)	-----			
Capacitance tolerance 电容偏差		$\pm 5\%$				
Loss angle tangent 损耗角正切		≤ 0.0020 (100 Hz)				
结	Shape 外形	See right picture 见右图				
	Condenser fuse 电容器芯子	Have self-healing 具有自愈性				
结	Case 外壳	White of plastics outer shell 白色塑料外壳			Drafts system: 拟制：林海燕	Name: : CBB60 metallized polypropylene film capacitor. 名称：CBB60型金属化聚丙烯薄膜电容器



构	Terminals 引出	250# Terminal 2+2 250型端子 2+2	Approval 核准:	Wenling jiyang capacitor co.,LTD 温岭市嘉洋电容器有限公司
	Filling 填充料	Epoxy resin 环氧树脂		