

D7010M12B/S

1. MODEL NUMBER	D7010M12B(T1)	D7010M12S(T1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	70 x 70 x 10 mm (2.8 x 2.8 x 0.4 inch)	70 x 70 x 10 mm (2.8 x 2.8 x 0.4 inch)
4. RATED VOLTAGE	5 VDC	5 VDC
5. OPERATING VOLTAGE RANGE	9 V ~ 15V	9 V ~ 15V
6. START-UP VOLTAGE	15 V / Min.	15 V / Min.
7. RATED MOTOR SPEED	3200 RPM ±10%	3200 RPM ±10%
8. AIR FLOW	22.2 CFM (0.60 m ³ /Min.)	22.2 CFM (0.60 m ³ /Min.)
9. STATIC PRESSURE	2.30 mm/H ₂ O (0.091 inch/H ₂ O)	2.30 mm/H ₂ O (0.091 inch/H ₂ O)
10. RATED CURRENT	0.25Amp ±10%	0.25 Amp ±10%
11. RATED INPUT POWER	3.0 Watts ±10%	3.0 Watts ±10%
12. NOISE LEVEL	31.4dB(A)	31.4 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	48 gm	48 gm

