



**C 0580 - 09 F A A S L O**

- 1. PRODUCTS:  
C: Connector
- 2. SERIES NO.:  
0580
- 3. CONTACT NO.:  
09, 15, 25, 37
- 4. CONTACT TYPE:  
F: Female
- 5. BODY OPTION:  
A: Metal Shell W/O S/R  
B: Metal Shell W/Metal S/R  
C: Metal Shell W/Plastic S/R  
D: Plastic Shell W/O S/R  
E: Plastic Shell W/Metal S/R  
F: Plastic Shell W/Plastic S/R
- 6. MOUNTING OPTION:  
A: Through Hole
- 7. CONTACT PLATING:  
S: Selective Gold  
G: Gold Flash  
A: Gold 50"  
B: Gold 100"  
C: Gold 150"  
D: Gold 300"
- 8. INSULATOR COLOR:  
B: Black  
G: Grey  
L: Blue
- 9. FILL IT WITH "0"

**SPECIFICATION :**  
 .INSULATOR MATERIAL : PBT & G/F REINFORCED,UL 94-V0  
 .CONTACT MATERIAL : PHOSPHOR BRONZE,SELECTIVE GOLD PLATED OVER NICKEL  
 .STRAIN RELIEF MATERIAL : PBT & G/F REINFORCED,UL 94-V0  
 .SHELL MATERIAL : SPCC,TIN OR NICKEL PLATED  
 .CURRENT RATING : 1 AMP.  
 .INSULATION RESISTANCE : 1000M ΩMIN. (AT 500 V DC)  
 .DIELECTRIC WITHSTANDING VOLTAGE : AC 500V MIN. (FOR 1 MIN)  
 .OPERATING TEMPERATURE : -25°C TO 85°C  
 .CONTACT RESISTANCE : 15m ΩMAX  
 .WIRE SIZE : AWG 26 & 28 STRANDED , 1.27mm CONDUCTOR CENTRE FLAT CABLE



37	63.50(2.500)	69.40(2.732)	49.86/(1.963)	47.09/(1.854)	54.60/(2.150)	57.10/(2.248)	54.84/(2.159)	59.08/(2.326)	60.73/(2.391)
25	47.04(1.852)	53.09(2.090)	33.24/(1.309)	30.47/(1.200)	38.14/(1.502)	40.90/(1.610)	38.38/(1.511)	42.52/(1.674)	44.27/(1.743)
15	33.32(1.312)	39.10(1.539)	19.39/(.763)	16.62/(.654)	24.00/(.945)	26.60/(1.047)	24.66/(.971)	28.80/(1.134)	30.53/(1.202)
9	24.99/(.984)	30.80(1.212)	11.08/(.436)	8.31/(.327)	16.10/(.634)	18.60/(.732)	16.33/(.643)	20.47/(.806)	22.20/(.874)
NO. OF POSITIONS	±0.13 A (±.005)	±0.25 B (±.010)	±0.13 C (±.005)	±0.13 D (±.005)	±0.25 E (±.010)	±0.25 F (±.010)	±0.25 H (±.010)	±0.13/(.005) REAR MOUNTING	±0.13/(.005) FRONT MOUNTING



**RECOMMENDED PANEL CUTOUT DIMENSIONS**