



**Technical specification:**

Degree of protection: IP 67, in mated condition  
IEC 60529

Temperature range: -30°C ... +120°C

**Materials:**

Protecting cap: PA GF, UL 94 V-0

**Installation specification:**

Recommended torque: 0,4 Nm

Part no:	Description:	Colour:
42-11772	Protecting cap M8x1 female socket	black
42-11860	Protecting cap M8x1 female socket	white RAL 9016

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index a: Ä6174 rbo 02.06.16 Part no. added	dim. in mm	title: <b>Protection cap M8x1, female socket</b>									
		<table border="1"> <thead> <tr> <th></th> <th>date</th> <th>name</th> </tr> </thead> <tbody> <tr> <td>drawn</td> <td>31.10.12</td> <td>Kniesburges</td> </tr> <tr> <td>appd.</td> <td>31.10.12</td> <td>Franz</td> </tr> </tbody> </table>			date	name	drawn	31.10.12	Kniesburges	appd.	31.10.12	Franz
		date	name									
	drawn	31.10.12	Kniesburges									
appd.	31.10.12	Franz										
general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm		part no: see table										
<small>THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH</small>												