



P.C.B. LAYOUT(REF)

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U≤30	±0.20	0~30	±0.25
30<U≤53	±0.25	over 30~53	±0.30
53<U≤70	±0.30	over 53~70	±0.35
70<U≤90	±0.35	over 70~90	±0.44
90<U≤115	±0.44	over 90~115	±0.55
115<U≤150	±0.55	over 115~150	±0.70
150<U≤200	±0.70	over 150~200	±0.85
200<U≤250	±0.85	over 200~250	±1.00
250<U≤320	±1.00	over 250~320	±1.20

NOTES:

1. Rating: 250V 10A
PITCH: 5.00mm
2. Insulation Withstands Voltage:
AC 1500V at 1 minute
3. Insulation Resistance:
1000MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+130°C
5. *: 另附, 不裝在產品上, 分开包裝
6. RoHS compliance

ITEM	NAME OF PART	MATERIAL	NOTES
3	CLIP *	STAINLESS STEEL	ZINC PLATED
2	CLAMP	COPPER ALLOY	Tin PLATED
1	HOUSING	PBT(G15)	

DWG.	Tuo.Y	DATE	15.04.17	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	4:1 (:)		
APP.		DATE					

	REV.	CONTENT	CHK.	DATE		DINKLE ENTERPRISE CO.,LTD	NAME	RYPS-08