





CLASSIFICATION 類別		TIMER 限時繼電器			MULTIRANGE TIMER 多段式限時繼電器						
MODEL 型號		AH3-□			H3BA-□ (ST4P-□)			H3CR-□		H3CR-A8	
APPEARANCE 外觀											
DIMENSIONS 尺寸		50H×40W×57.5D			48H×48W×93.5D			48H×48W×81.6D		48H×48W×81.6D	
MOUNTING & SOCKET 安裝與其底座	SURFACE(-N) 露出型	PF083A(E)			PF113A(E)	P2CF08 PS-08			PS-08		PF113A(E)
	FLUSH(-Y) 埋入型	US-08 P3G-08			US-11	US-08 P3G-08			US-08 P3G-08		US-11
FULL TIMING RANGE 時間範圍		SEC:1,3,6,10,12,30,60 MIN:3,6,10,12,30,60 HR:3,6,10,12,30			0.5SEC~100HRS			0.5SEC~300HRS		0.5SEC~300HRS	
RATED VOLTAGE 額定電壓					24 to 240V DC/AC DC(V):12,24,48 AC(V):24,50,110,220			100 to 240 VAC/100 to 125 VDC 24 to 48 VAC/12 to 48 VDC AC(V) 110V, 220V DC(V) 12V, 24V			
INDICATOR OPERATING 指示燈動作		ON-UP Operating ON-UP 指示			Time Operating flicker 計時中閃爍指示			Time Operating flicker 計時中閃爍指示			
O/P CONTACT 輸出接點	MODEL 型號	AH3-1	AH3-2	AH3-3	H3BA	H3BA-8	H3BA-8H	H3CR-A		H3CR-A8	
	TIME LIMIT 1C 限時 1C	5A		5A			5A				
	TIME LIMIT 2C 限時 2C		5A		5A	5A		5A(AC250)		5A(AC250)	
	INSTANTANEOUS 1C 瞬時 1C			5A			5A				
LIFE 壽命	MECHANICAL 機械	5×10 ⁶ times			5×10 ⁷ times			10 ⁷ times		10 ⁷ times	
	ELECTRICAL 電氣	10 ⁵ times			10 ⁵ times			10 ⁵ times		10 ⁵ times	
ACCURACY 精確度	REPEAT ERROR 重複誤差	±1% max			±1% max			±1% max		±1% max	
	SETTING ERROR 設定誤差	±10% max			±5% max			±5% max		±5% max	
	VOLTAGE ERROR 電壓誤差	±1% max			±1% max			±1% max		±1% max	
	TEMP. ERROR 溫度誤差	±2% max			±2% max			±2% max		±2% max	
RESET TIME 復位時間		0.1 sec max			0.5 sec max			0.5 sec max		0.5 sec max	
CONSUMED POWER 消耗功率		2VA			100~240VAC:1VA 12VDC,24~240VDC:1.5W						
AMBIENT TEMPERATURE 環境溫度		-10℃~+55℃			-10℃~+55℃			-10℃~+55℃		-10℃~+55℃	
AMBIENT HUMIDITY 濕度		48~85%RH			35~85%RH			35~85%RH		35~85%RH	
WEIGHT 重量		160g			100g			100g		100g	
CONNECTION DIAGRAMS & TIMING CHART 接線圖與時序圖		39D	39E	39F	40F	40H	40G	40F		40E、J	