



THB.387.B5A

TH387 - mini-Plug&Socket connector IP66/IP68

MADE IN ITALY



IP68 IP66



INSTALLATION INSTRUCTIONS

- 606004000 IST TH387 lungo PDF • 362 KB
- IST TH387 PDF • 452 KB
- Techno Assembly TH387 PDF • 1 MB
- Guidelines Installation PDF • 753 KB


CERTIFICATIONS AND TEST REPORTS

- CE-TH387 DOCX • 352 KB
- TH387 CA0205037 PDF • 316 KB

MARKETING COLLATERALS

- cartolina 210x105 ita 2 PDF • 82 KB
- maggiopubblicita PDF • 1 MB
- Pannello 2 PDF • 365 KB

DRAWINGS

- THB387B5A STEP
• 4 MB •  CONFIDENTIAL DOCUMENT

GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP66/IP68 Plug&Socket circular connectors
Product name (Series)	TH387 - mini-Plug&Socket connector IP66/IP68
Product configuration	Socket connector (cable-to-cable)
Type of Fixation	With quick-fix mounting clip • Mounting clip to be ordered separately (code 6000302CC).
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 23 mm x 85 mm (when plug-socket matched)


ELECTRICAL CHARACTERISTICS

Number of poles	5
Contact marking	1 - 2 - 3 - 4(E) - 5
Type of connection	screw (M2 - max. 0.2 Nm)
Operating current	max. 17.5A
Operating voltage	max. 450V AC
Impulse withstand voltage	4KV

 Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP66/IP68 (30m,3h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

 Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.25 mm ² - 1.5 mm ²
Wire cross-section min. - max. (Solid cable)	0.25 mm ² - 1.5 mm ²
Cable diameter min. - max.	7.0 mm - 12.0 mm • For cables with diameter For smaller cables please take the proper accessory. For cables with diameter 14.0 mm take the code 604004900.

MATERIAL CHARACTERISTICS

Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	TPE-S
Grommets	TPE-S
Contacts	CuZn (silver plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free - Silicone Free



T marking	T 125°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

i Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009
------------------------	---------------

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 products/box
Unit weight	18,2 gram/product
Box dimension	300 x 200 x 160