



FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

CONTACT COMPOSITION

序号	型号 Type		
1	1NO1NC		
2	2NC		
3	2NO		

PART NUMBER: LAS0-B3Y-□X/◇◆/△

"□"	CONTACT STRUCTURE
11	1NO 1NC
20	2NO
02	2NC

THE COMBINATION MODE CAN BE SELECTED ACCORDING TO THE NEEDS. IF SLOW MOVING STRUCTURE IS NEEDED, PLEASE ADD "M" BEFORE "□"

"◇"	OPERATION POSITION
2	TWO POSITION

"◆"	OPERATION TYPE
1	MAINTAIN
3	RETURN

"△"	CAP COLOR
R	RED
G	GREEN
N	BLACK

SPECIFICATIONS:

- SWITCH RATING: $U_i: 500V, I_{th}: 10A$.
- ELECTRICAL LIFE: $\geq 50,000$ cycles.
- CONTACT RESISTANCE: $\leq 50m\Omega$.
- INSULATION RESISTANCE: $\geq 100M\Omega(500VDC)$.
- DIELECTRIC STRENGTH: 3000V, RMS 50Hz, 1min.
- OPERATING TEMPERATURE: $-25^{\circ}C \sim +55^{\circ}C$ (NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON).
- TORQUE: 0.6Nm Max. APPLIED TO NUT.
- FRONT PANEL PROTECTION DEGREE: IP40.
- TERMINAL TYPE: THREAD CONNECTION, DIAMETER OF WELDED WIRE: (2X1.5mm²).
- OPERATING REQUIREMENT: 90° ROTATION REQUIRES, ROTATION IN PLACE.
- GENERAL TOLERANCE: 0-18mm=±0.25, 18-80mm=±0.52.

MATERIALS:

- CONTACT: SILVER ALLOY.
- BUTTON: AL ALLOY/POM.
- BODY: PA.
- BASE: PC.

BRAND 品牌		红波按钮制造有限公司	
ONPOW 欧宝龙®		ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.	
TITLE 名称	LAS0-B3 SERIES SELECTOR SWITCH		UNIT 单位 mm
DWG NO. 图号	LAS0-B3Y-X TWO POSITION	SCALE 比例 1:1	SIZE 图纸 A4
FILE NAME 档案名称	LAS0-B3Y-X .DWG	DRAWN 制图 HCP 2023/07/15	SHEET 张 1/1
			REV. 更改 1