

Extruded heatsinks for PCB mounting

- for semiconductor clip-mounting
- special lengths and transistor drillings upon request
- **P** = raised retaining stud, **E** = mounting method

art. no.	l [mm]	R _{th} [K/W]	⌀
SK 104 25,4 ...	25.4	14	TO 220
SK 104 38,1 ...	38.1	11	TO 220
SK 104 50,8 ...	50.8	9	TO 220
SK 104 63,5 ...	63.5	8	TO 220

please indicate: ... mouting method
STC = with solder pin
STIC = with solder pin and insulating washer
STCB = with threaded bolt M3, brass

surface: black anodised

- for semiconductor screw-mounting
- special lengths and transistor drillings on request
- **E** = mounting method

art. no.	l [mm]	R _{th} [K/W]	⌀
SK 104 25,4 ...	25.4	14	SOT 32/ TO 220/ TO 3 P
SK 104 38,1 ...	38.1	11	SOT 32/ TO 220/ TO 3 P
SK 104 50,8 ...	50.8	9	SOT 32/ TO 220/ TO 3 P
SK 104 63,5 ...	63.5	8	SOT 32/ TO 220/ TO 3 P

please indicate: ... mouting method
STS = with solder pin
STIS = with solder pins and insulating washer
STSB = with threaded bolt M3, brass

surface: black anodised

Lock-in transistor fixing spring
 Profiles for PCB components
 Vibration dampers
 Heatsinks with threaded rail

→ A 117 – 119 Miniature distance sleeves
 → A 91 Thermal conductive glue
 → E 39 Thermal conductive paste
 → A 92 Technical introduction

→ E 32
 → E 21 – 22
 → E 19 – 20
 → A 2 – 7