

datasheet for KLEPS 2700  
 article number: 972307100



<b>product description:</b>	order number: 972 307-100
<b>description:</b>	Safety clamp-type test probe with split test clamp. The sprung stainless steel tip can contact insulated leads with cross-sections between 0.25 mm <sup>2</sup> and 1.5 mm <sup>2</sup> (3.5 mm diameter) without the need to strip them. 4 mm diameter brass socket connection.
<b>typ:</b>	KLEPS 2700 schwarz/black
<b>system:</b>	4 mm safety system
<b>order number:</b>	972 307-100
<b>clamping range:</b>	1.5 mm <sup>2</sup>
<b>clamping typ:</b>	stainless steel tip
<b>color</b>	●
<b>other color versions:</b>	● ●
<b>technical data</b>	
<b>measurement category</b>	CAT III
<b>norm</b>	DIN EN 61010-031
<b>type of termination:</b>	4 mm socket
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b>	10 A
<b>contact resistance:</b>	100 mOhm
<b>material</b>	
<b>contact material:</b>	needle (stainless steel)
<b>contact surface material:</b>	nickel-plated
<b>housing material:</b>	PBT
<b>environmental conditions:</b>	
<b>temperature range:</b>	-25 °C to +80 °C
<b>inflammable class:</b>	
<b>housing:</b>	94 HB
<b>drawing</b>	
	